



|           | Omschrijving       | l/min      | bar     | inlaat       | bypass     | uitlaat  | temp | O-ring | materiaal | ref PA    | PA-nummer  |
|-----------|--------------------|------------|---------|--------------|------------|----------|------|--------|-----------|-----------|------------|
| 7036      | Ontlastingsventiel | 80 l/min   | 275 bar | 1/2 NPTF     | 1/2 NPTF   | 1/2 NPTF | 90°  | FPM    | SS        | ////      | ////////   |
| 7046      | Ontlastingsventiel | 80 l/min   | 400 bar | 1/2 BSPF     | 1/2 BSPF   |          | 90°  | NBR    | SS        | VS400     | 60.0550.00 |
| 7085      | Ontlastingsventiel | 14 l/min   | 140 bar | 1/4 BSPM     | 1/8 BSPF + |          | 90°  | NBR    | Brass     | VS160     | 60.0560.00 |
| 7190      | Ontlastingsventiel | 25 l/min   | 345 bar | 3/8 BSPF     | 3/8 BSPF   | 3/8 BSPF | 60°  | NBR    | Brass     | VS350     | 60.0580.00 |
| 7196      | Ontlastingsventiel | 80 l/min   | 500 bar | 1/2 BSPF     | 3/8 BSPF   |          | 60°  | NBR    | Brass     | VS500     | 60.5200.00 |
| 32741     | Ontlastingsventiel | 200 l/min  | 180 bar | 3/4 NPTF     | 1/2 NPTF   |          | 90°  | NBR    | Brass     | VS200/180 | 60.5100.00 |
| 32741.BSP | Ontlastingsventiel | 200 l/min  | 180 bar | 3/4 BSPF     | 1/2 BSPF   |          | 90°  | NBR    | Brass     | VS200/180 | 60.5100.15 |
| 39228     | Ontlastingsventiel | 24 l/min   | 220 bar | 3/8 BSPF     | 3/8 BSPF   |          | 90°  | NBR    | Brass     | VS220     | 60.0515.00 |
| 39229     | Ontlastingsventiel | 24 l/min   | 220 bar | 2 x 3/8 BSPF | 3/8 BSPF   |          | 90°  | NBR    | Brass     | VS220     | 60.0525.00 |
| 39389     | Ontlastingsventiel | 24 l/min   | 150 bar | 3/8 BSPF     | 3/8 BSPF   |          | 90°  | NBR    | Brass     | VS170     | 60.0540.00 |
| 39430     | Ontlastingsventiel | 24 l/min   | 140 bar | 3/8 NPTM     |            |          | 60°  | NBR    | Brass     | VS140     | 60.1570.00 |
| 39440     | Ontlastingsventiel | 24 l/min   | 240 bar | 3/8 NPTM     |            |          | 60°  | NBR    | Brass     | VS240     | 60.1580.00 |
| 39518     | Ontlastingsventiel | 80 l/min   | 280 bar | 1/2 BSPF     | 1/2 BSPF   |          | 90°  | FPM    | SS        | VS26      | 60.1540.00 |
| 39560     | Ontlastingsventiel | 80 l/min   | 280 bar | 1/2 BSPF     | 1/2 BSPF   |          | 90°  | FPM    | SS        | VS80/280  | 60.0590.60 |
| 39579     | Ontlastingsventiel | 24 l/min   | 140 bar | 3/8 BSPM     |            |          | 60°  | NBR    | Brass     | VS140     | 60.1550.00 |
| 39580     | Ontlastingsventiel | 24 l/min   | 240 bar | 3/8 BSPM     |            |          | 60°  | NBR    | Brass     | VS240     | 60.1560.00 |
| 39585     | Ontlastingsventiel | 20 l/min   | 125 bar | 1/4 BSPF     | 1/4 BSPF   |          | 90°  | FPM    | SS        | VS100     | 60.0470.60 |
| 39625     | Ontlastingsventiel | 450 l/min  | 200 bar | 1-1/4 BSPF   | 1-1/4 BSPF |          | 90°  | NBR    | Brass     | VS450/200 | 60.4120.00 |
| 39660     | Ontlastingsventiel | 60 l/min   | 660 bar | 3/8 BSPF     | 1/2 BSPF   |          | 90°  | NBR    | SS/Brass  | VS660     | 60.0650.00 |
| 39705     | Ontlastingsventiel | 80 l/min   | 500 bar | 1/2 BSPF     | 3/8 BSPF   |          | 90°  | NBR    | Brass     | VS500     | 60.5212.00 |
| 890704    | Ontlastingsventiel | 1211 l/min | 138 bar | 2 NPTF       | 2 NPTM     | 2 NPTF   | 149° | FPM    | SS        | ////      | ////////   |
| 890709    | Ontlastingsventiel | 227 l/min  | 276 bar | 2 NPTF       | 2 NPTM     | 2 NPTF   | 149° | FPM    | SS        | ////      | ////////   |