



Drukreg- & ontlast vent. = Drukregel- & ontlastingsventiel

	Omschrijving	l/min	bar	inlaat	bypass	uitlaat	temp	O-ring	materiaal	ref PA	PA-nummer
7500.X	Drukreg- & ontlast vent. (2SFX)								Brass		
7500S	Drukreg- & ontlast vent. (2SF30GES)	23 l/min	140 bar	3/8 NPTM	3/8 NPTF	3/8 NPTM		NBR	Brass		
7576	Drukreg- & ontlast vent.	80 l/min	500 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	Brass	VB16	60.8000.00
7590	Drukreg- & ontlast vent.	200 l/min	150 bar	1 NPTF	1 NPTF	1 NPTF	90°	NBR	Brass	VB200/150	60.5000.00
7630	Drukreg- & ontlast vent.	40 l/min	350 bar	3/8 NPTM	1/2 BSPF	3/8 NPTF	90°	NBR	FBB	VB350	60.1750.00
7630.PRE	Drukreg- & ontlast vent.	40 l/min	350 bar	3/8 NPTM	1/2 BSPF	3/8 NPTF	90°	NBR	Brass	VB350	60.1800.00
7730	Drukreg- & ontlast vent., modulair	17 l/min	210 bar	1/2 NPTF	built in	3/8 NPTM	71°	NBR	FBB	////	////////
7850	Drukreg- & ontlast vent., modulair	23 l/min	275 bar	1/2 NPTF	built in	3/8 NPTM	71°	NBR	FBB	////	////////
7860	Drukreg- & ontlast vent. + injector	19 l/min	275 bar	1/2 NPTF	built in	3/8 NPTM	71°	NBR	Brass	////	////////
8700	Drukreg- & ontlast vent.	60 l/min	600 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	60°	NBR	SS 303	VB60/600	60.2600.00
32285	Drukreg- & ontlast vent.	25 l/min	160 bar	3/8 BSPM	3/8 BSPF	3/8 BSPM	90°	NBR	Brass	VB130	60.0300.00
32286	Drukreg- & ontlast vent.	25 l/min	70 bar	3/8 BSPM	3/8 BSPF	3/8 BSPM	90°	NBR	Brass	VB130	60.0300.50
32287	Drukreg- & ontlast vent. + regelbare injector	25 l/min	160 bar	3/8 BSPM	3/8 BSPF	3/8 BSPM	90°	NBR	Brass	VB130	60.0320.18
32319	Drukreg- & ontlast vent.	80 l/min	400 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	FPM	SS 303	VB80/400	60.0430.00
32692	Drukreg- & ontlast vent.	30 l/min	220 bar	3/8 BSPM	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	VB7	60.0700.00
32720	Drukreg- & ontlast vent. + handvat	30 l/min	220 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	VB9	60.2250.00
39226	Drukreg- & ontlast vent.	80 l/min	150 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	FPM	SS 316	VB80-AISI316	60.0450.00
39227	Drukreg- & ontlast vent.	80 l/min	280 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	FPM	SS 316	VB80-AISI316	60.0450.60
39269	Drukreg- & ontlast vent. + schakelaar + handvat	30 l/min	220 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	VB9	60.2350.00
39352	Drukreg- & ontlast vent.	25 l/min	220 bar	3/8 BSPM	3/8 BSPF	3/8 BSPM	90°	NBR	Brass	VB3	60.1900.00
39353	Drukreg- & ontlast vent.	30 l/min	220 bar	3/8 BSPM	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	VB5	60.1300.00
39355	Drukreg- & ontlast vent.	80 l/min	400 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	SS 303	VB43	60.1450.00
39356	Drukreg- & ontlast vent.	80 l/min	560 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	SS 303	VRP600	60.5400.00
39439	Drukreg- & ontlast vent.	30 l/min	220 bar	pump	built in	3/8 BSPF	90°	NBR	Brass	VB55	60.1350.00
39480	Drukreg- & ontlast vent. + schakelaar	30 l/min	220 bar	3/8 BSPM	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	VB8	60.1280.00
39516	Drukreg- & ontlast vent.	450 l/min	200 bar	1-1/4 BSPF	1-1/2 BSPF	1-1/4 BSPF	90°	NBR	Brass	VB450/200	60.4020.00
39550	Drukreg- & ontlast vent., zero bypass	40 l/min	280 bar	3/8 BSPF	2 x 3/8 BSPF	3/8 BSPF	60°	NBR	Brass	PULSAR	60.2400.00
39590	Drukreg- & ontlast vent.	200 l/min	280 bar	1 BSPF	1 BSPF	1 BSPF	90°	NBR	Brass	VB200/280	60.4300.00
39602	Drukreg- & ontlast vent.	80 l/min	150 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	SS 303	VB80/150	60.0430.15
39635.R	Drukreg- & ontlast vent.	80 l/min	160 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	Brass	VB85	60.4023.00
39640.R	Drukreg- & ontlast vent.	80 l/min	280 bar	1/2 BSPF	1/2 BSPF	1/2 BSPF	90°	NBR	Brass	VB85	60.0423.60
39665	Drukreg- & ontlast vent.	30 l/min	220 bar	pump	built in	3/8 BSPF	90°	NBR	Brass	VB56	60.1372.10
39715.R	Drukreg- & ontlast vent., witte veer	40 l/min	160 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0000.00
39716.R	Drukreg- & ontlast vent., blauwe veer	40 l/min	280 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0000.60
39716.RT	Drukreg- & ontlast vent. + 1/4 aansluiting	40 l/min	280 bar	2 x 3/8 BSPF	3/8 BSPF	2 x 3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0045.60
39717.R	Drukreg- & ontlast vent. + handvat	40 l/min	160 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0007.00

39717.RT	Drukreg- & ontlast vent. + 1/4 aansluiting	40 l/min	280 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0016.00
39718.R	Drukreg- & ontlast vent. + handvat	40 l/min	280 bar	3/8 BSPF	3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0007.60
39718.RMS	Drukreg- & ontlast vent. + schakelaar + handvat	40 l/min	280 bar	3/8 BSPF	2 x 3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0006.60
39718.RT	Drukreg- & ontlast vent. + handvat + 1/4 aansluitin	40 l/min	280 bar	2 x 1/8 BSPF	2 x 3/8 BSPF	3/8 BSPF	90°	NBR	Brass	PULSAR4	60.0016.60